

REVOTROPIX PAULOWNIA SAWN TIMBER

PRODUCT SHEET

SAWN TIMBER

Commercial Species	Revotropix Paulownia
Thickness (mm)	22 to 100
Width (mm)	22 to 125
Length (mm)	150 to 2400
Cut	Flat Sawn
Moulding	Surfaced Four Sides (S4S), Surfaced Two Sides (S2), Finger Joint Stock, Edge-Joint Lamination Board
Grading	Malaysian Grading Rules (MGR)

TECHNICAL SPECIFICATION

MOE	4680 N/mm ²
MOR	41.59 N/mm ²
Shear	5.56 N/mm ²
Compressive Strength	20.79 N/mm ²
Density	304 kg/m ³
Specific Gravity	0.266

COMMON APPLICATIONS

Furniture, linings, mouldings, frames, crate, craft and art, indoor structure, blockboard, scantilings


ECOPENEER SDN BHD 202101013826 (1414125-V)


Headquarters

Level 17, Top Glove Tower, No. 16, Persiaran Setia Dagang, Setia Alam, Seksyen U13, 40170 Shah Alam, Selangor Darul Ehsan, Malaysia.

Factory

1778-1779, Jalan Tampin-Gemas, 73400 Gemas, Negeri Sembilan.

 +6 03 3359 1166

 +6 03 3358 0303

 info@ecopeneer.com

 www.ecopeneer.com